



淮安市上研化工有限公司

## AMORSO-335G

### Acrylic Leveling Agent

#### Introduction:

AMORSO-335G is a non-organic silicon organic copolymer used to control the fluidity of solvent-borne coatings. To improve the flatness and scratch resistance, it can also prevent the paint from producing pinhole, crater and other defects, especially good effect for paint, wood paint or forced drying coating.

#### Features:

It is a newly developed product, it's not just suitable for the general non-aqueous paint, but also for high polarity polyester resin, epoxy resin and polyurethane system coatings, so a little addition has a good effect. It is recommended to dilute before adding.

It can not only increase the dispersion and anti-settling ability of pigment, but also increase the covering power of coating film. It can increase the warm and moist effect of the filler.

#### Technical data:

Composition: acrylics

Appearance: light color liquid

Non-volatile part: 50%±1.5%

Acid value: ≤5

#### Applications:

- solvent-borne/UV
- industrial baking paint
- plastic paint
- coil coating
- car paint
- car repair paint
- anti-corrosion coating

#### Usage and dosage:

- It can be added before or after the grinding stages.
- 0.1%-0.5% of the total weight, increase or decrease the addition amount based on coating composition or its requirement.

#### Package:

25KG barrel

[The above data and specification is only for reference, customer should do the test based on different application and requirement to see if it is appropriate and suitable for their usage. ]

ADD: 2F, building D, Dibao Industrial Park, No. 1188, Hongqiao Road, Yushan Town, Kunshan City, Jiangsu Province POST CODE: 215300

TEL: 0512-57758550 FAX: 0512-57508876

email: sales@amorso.com