文件编号: SY-TDS-TE0001 日 期: 2020/08/12



淮安市上研化工有限公司

AMORSO-388

Fluorine Modified Acrylic Leveling Agent

Introduction:

AMORSO-388 is an excellent flow flat agent, it is used in solvent-borne matting paint, color paint, excellent defoaming effect. It can also prevent the occurrence of crater, fish eye, pinhole and crust.

Features:

- excellent flow flatting effect
- excellent defoaming effect
- can prevent crater, fish eye, pinhole, anti-crust and other phenomena

Technical data:

Active substance: 73%±3% Solvent: esters

Applications:

- •solvent-borne
- industrial baking paint
- plastic paint
- wood paint
- coil coating
- •car paint
- car repair paint
- printing ink
- epoxy flooring
- anti-corrosion coating

Usage and dosage:

- •It is recommended to dilute with solvent by 1:1, it can be added before or after the grinding stages.
- •0.1%-1% of the total weight.

Package:

25KG barrel

Attentions:

Excessive addition or uneven dispersion may cause shrinkage.

[The above data and specification is only for reference, customer should do the test based on different application and requirement to see if it is appropriate and suitable for their usage.]

ADD: 2F, building D, Dibao Industrial Park, No. 1188, Honggiao Road, Yushan Town, Kunshan City, Jiangsu Province POST CODE: 215300

TEL: 0512-57758550 FAX: 0512-57508876 email: sales@amorso.com

页码: 1/1, 共1页

文件编号: SY-TDS-TE0001 日 期: 2020/08/12



淮安市上研化工有限公司

[The above data and specification is only for reference, customer should do the test based on different application and requirement to see if it is appropriate and suitable for their usage.]

email: sales@amorso.com

ADD: 2F, building D, Dibao Industrial Park, No. 1188, Hongqiao Road, Yushan Town, Kunshan City, Jiangsu Province POST CODE: 215300

TEL: 0512-57758550 FAX: 0512-57508876

页码: 1/1, 共1页