



淮安市上研化工有限公司

AMORSO-265

Organofluorosilicone Defoamer

Introduction:

AMORSO-265 is a highly effective fluoro-contained defoamer with great miscibility. Used in prime paint, finish paint, high photocurrent coating. It is recommended to use for high photocurrent coating with dosage below 0.2%. It is applied in solvent-borne system, such as: PU, UV curing, also applied in high viscosity system, such as printing ink and epoxy floor.

Features:

- superior defoaming ability and good miscibility
- improve the leveling ability
- improve the smooth effect
- do not affect the recoating ability

Technical data:

Composition: organic fluorosilicone compound

Non-volatile part: 3.5%±1%

Appearance: light color liquid

Solvent: esters/alcohols

Applications:

- solvent-borne/UV
- plastic paint
- wood paint
- car paint
- car fixing paint
- coil coating
- printing ink
- epoxy floor
- anti-corrosion coating

Usage and dosage:

General dosage is 0.1~2% of total weight, add quick dispersant directly.

Package:

25KG barrel

[The above data and specification is only for reference, customer should do the test based on different application and requirement to see if it is appropriate and suitable for their usage.]

ADD: 2F, building D, Dibao Industrial Park, No. 1188, Hongqiao Road, Yushan Town, Kunshan City, Jiangsu Province POST CODE: 215300

TEL: 0512-57758550 FAX: 0512-57508876

email: sales@amorso.com



淮安市上研化工有限公司

[The above data and specification is only for reference, customer should do the test based on different application and requirement to see if it is appropriate and suitable for their usage.]

ADD: 2F, building D, Dibao Industrial Park, No. 1188, Hongqiao Road, Yushan Town, Kunshan City, Jiangsu Province POST CODE: 215300

TEL: 0512-57758550 FAX: 0512-57508876

email: sales@amorso.com