



淮安市上研化工有限公司

## AMORSO-628

### Solvent-borne Anti-scratch Wax

**Introduction:**

Good dispersion and suspension.

**Technical data:**

Non-volatile part: tissuemat E

Volatile part: xylene, butyl acetate

Appearance: light gel

Non-volatile part: 26%  $\pm$ 2%

**Applications:**

Giving the film better scratch resistance and wear resistance.

Improving the matting effect.

**Usage and dosage:**

Add slowly in the stirring process first, then increase the speed of stirring.

Perfect for pre-process addition to ensure complete dispersion.

1%~8% of total weight.

**Package:**

18KG iron barrel

**Attentions:**

Avoid direct sunlight, store in cool place, the storage temperature and stirring temperature should not exceed 45°C. Avoid light and keep away from the source of heat. It can be kept for one year in The sealed container.

The above instructions are for reference only, they do not have any guarantee effect. Please test their applicability first.

[The above data and specification is only for reference, customer should do the test based on different application and requirement to see if it is appropriate and suitable for their usage. ]

ADD: 2F, building D, Dibao Industrial Park, No. 1188, Hongqiao Road, Yushan Town, Kunshan City, Jiangsu Province POST CODE: 215300

TEL: 0512-57758550 FAX: 0512-57508876

email: sales@amorso.com