



淮安市上研化工有限公司

## AMORSO-113

### Silicon Handfeel Scratch Resistant Leveling Agent

#### Introduction:

AMORSO-113 is a new type of light curing, PU and other rapid leveling, strong versatility and low foam stability.

#### Features:

- reduce surface tension, improve smoothness and scratch resistance, low foam stability, help substrate wetting.
- good miscibility with each resin, more prominent performance in epoxy resin system.

#### Technical data:

Composition: organosiloxane  
Active substance: 100%

Appearance: light liquid/solid  
Solvent : /

#### Applications:

- industrial baking paint
- wood paint
- car paint
- UV paint
- epoxy flooring

#### Usage and dosage:

The additive can be incorporated during any stage of the production process after dilution.  
0.1%-1% of the total amount of formula.

#### Package:

25KG plastic or iron barrel  
200KG iron drum

#### Storage and transportation:

Turbidity and stratification may occur in storage and transportation when below 15°C, please heat up to 20°C before use, and stir well.

#### Special reminder:

AMORSO-113 may appear turbid and gray appearance which does not affect the application of the product.

[The above data and specification is only for reference, customer should do the test based on different application and requirement to see if it is appropriate and suitable for their usage. ]

ADD: 2F, building D, Dibao Industrial Park, No. 1188, Hongqiao Road, Yushan Town, Kunshan City, Jiangsu Province POST CODE: 215300

TEL: 0512-57758550 FAX: 0512-57508876

email: sales@amorso.com