文件编号: SY-TDS-TE0001 日 期: 2020/08/12



淮安市上研化工有限公司

AMORSO-471C

High Efficiency Adhesion Promoter

Features:

- good bending performance improvement
- •bond directly with metal, plastic and other substrates to enhance adhesion; excellent adhesion effect for stainless steel, aluminum, cold-rolled steel, galvanized steel, electroplated and other substrate (including after immersion and condensation test adhesion); good adhesion effect for engineering plastic substrate
- •make the film obtain excellent wear resistance and scratch resistance and improve the film's flexibility, anticorrosion, chemical resistance

Technical data:

Composition: acidic polymer with hyperbranched polyester as main chain

Solvent: alcohols

Active substance: 48%±3% Acid value: >60

Applications:

- thermoplastic coating ,2PK-PU, baking paint, soluble form waterborne paint, light curing paint, etc.
- 2PK-PU
- paint
- solvent-assisted waterborne paints
- light curing paint

Usage and dosage:

- •0.3%-3% of the total formula.
- •It is recommended to use alcohols or esters to dilute by 1:1 before use.

Package:

25KG plastic or iron barrel 200KG iron drum

Warranty:

Sealed to store for 12 months

[The above data and specification is only for reference, customer should do the test based on different application and requirement to see if it is appropriate and suitable for their usage.]

ADD: 2F, building D, Dibao Industrial Park, No. 1188, Hongqiao Road, Yushan Town, Kunshan City, Jiangsu Province POST CODE: 215300

TEL: 0512-57758550 FAX: 0512-57508876 email: sales@amorso.com

页码: 1/1, 共1页